

# Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-424-9300

Product Code:

Product Name: BEESWAX

Effective Date: 03/04/08 Date Printed: 03/04/08 MSDS #:

## 1. Ingredients

<u>Name</u>	<u>CAS#</u>	<u>OSHA-PEL</u>	<u>ACGIH-TLV</u>	<u>%</u>
Yellow Beeswax	8012-89-3	N.E.	N.E.	100

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). In addition, other substances not 'Hazardous' per this OSHA Standard may be listed. Where proprietary ingredient shows, the identity may be made available as provided in this standard.

## 2. Physical Data

MELTING POINT:	62-65 Deg. C
BOILING POINT:	Not determined
VAPOR PRESSURE:	Not determined
VAPOR DENSITY:	Not determined
SOLUBILITY IN WATER:	Insoluble
SPECIFIC GRAVITY:	0.95
APPEARANCE:	Yellow semi-hard wax
ODOR:	Characteristic

## 3. Fire And Explosion Hazard Data

FLASH POINT:	470 Deg. F
METHOD USED:	Cleveland open cup (ASTM D-92)

### FLAMMABLE LIMITS

LEL:	N.A.
UEL:	N.A.

EXTINGUISHING MEDIA: Foam, water fog, dry chemical, carbon dioxide or alcohol foam.

FIRE & EXPLOSION HAZARDS: Do not mix with strong oxidants.

FIRE-FIGHTING EQUIPMENT: No acute hazard.

#### **4. Reactivity Data**

Page 2 of 3.

STABILITY: Stable under normal temperatures and pressures.

CONDITIONS TO AVOID: Strong oxidizing agents.

INCOMPATIBILITY (SPECIFIC MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: None

HAZARDOUS POLYMERIZATION: Will not occur.

#### **5. Environmental and Disposal Information**

ACTION TO TAKE FOR SPILLS / LEAKS: Sweep up spilled material and place in suitable containers for recycling or disposal. Allow hot material to cool before disposal.

DISPOSAL METHOD: Dispose of as per Federal, State, County and Local regulations.

#### **6. Health Hazard Data**

EYE: Cold material may be an irritant as a foreign object. Hot material will cause burns.

SKIN CONTACT: No known hazard for cold material. Possible skin burns from hot or over heated material.

INGESTION: No known specific effects to humans.

INHALATION: Minimal risk under normal usage rate. However, inhaling high vapor concentrations (greater than approximately 1000 ppm) when the product is at liquid state under high temperatures may be irritating to the eyes and respiratory tract and might affect central nervous system.

#### **7. First Aid**

EYES: Flush eyes with large amounts of water until irritation subsides. If hot material gets in eyes, cool with water and consult a physician.

SKIN: If hot material contacts skin, cool as rapidly as possible with water. Do not attempt to remove the

material. Seek medical aid.

INGESTION: If swallowed, induce vomiting. Give 2 to 4 glasses of water. Get prompt medical attention.

## 8. Handling Procedures

EXPOSURE GUIDELINE(S): See Section 1 (if any).

RESPIRATORY PROTECTION: Solid product: For normal operations, no respiratory is required. Molten product: An air purifying respirator designed for organic vapors should provide adequate protection.

SKIN PROTECTION: None required under normal conditions.

EYE PROTECTION: Safety goggles.

### **REGULATORY INFORMATION: (Not meant to be all-inclusive - selected regulations represented.)**

NOTICE: The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations. See MSD Sheet for health and safety information.

### **U.S. Regulations:**

TSCA STATUS: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA TITLE III: Section 313 reportable ingredients:

<u>Component</u>	<u>CAS#</u>	<u>Maximum %</u>
1,2,4 Trimethylbenzene	95-63-6	2.96