

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-424-9300

Product Code:

Product Name: Edge Kote (various colors)

Effective Date: 03/04/08 Date Printed: 03/04/08 MSDS #:

1. Ingredients

<u>Name</u>	<u>CAS#</u>	<u>OSHA-PEL</u>	<u>ACGIH-TLV</u>	<u>%</u>
Acrylic polymer	Not hazardous	None established	None established	30 ó 60
Iron oxide	1309-37-1	10 mg/m3(as Fe, total particulate)	None established	1.5 ó 3.0
Iron oxide	51274-00-1	10 mg/m3(as Fe, total particulate)	None established	1.0 ó 2.0
Water	7732-18-5	None established	None established	35.0 ó 67.5

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). In addition, other substances not 'Hazardous' per this OSHA Standard may be listed. Where proprietary ingredient shows, the identity may be made available as provided in this standard.

2. Physical Data

BOILING POINT: > 210 Deg.F
 VAPOR PRESSURE: Not done
 VAPOR DENSITY: Not done
 SOLUBILITY IN WATER: Dispersible
 SPECIFIC GRAVITY: 1.10 - 1.15
 APPEARANCE: Variously colored liquids
 ODOR:

3. Fire And Explosion Hazard Data

FLASH POINT: Non-flammable
 METHOD USED: N/A

FLAMMABLE LIMITS

LFL: N/A
 UFL: N/A

EXTINGUISHING MEDIA: Use foam, Carbon dioxide, dry chemical or water spray on surroundings.

FIRE & EXPLOSION HAZARDS: Not a fire or an explosion hazard. However, material can spatter above 212 Deg.F.

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-424-9300

Product Code:

Product Name: Edge Kote (various colors)

Effective Date: 03/04/08 Date Printed: 03/04/08 MSDS #:

Polymer film can burn. In extreme cases, thermal decomposition may yield toxic fumes.

FIRE-FIGHTING EQUIPMENT: If material is involved in fire, wear NIOSH approved self-contained breathing apparatus. Use water spray to cool fire exposed containers.

4. Reactivity Data

STABILITY: Stable

(CONDITIONS TO AVOID): Temperatures over 350 Deg.F. Keep from freezing.

INCOMPATIBILITY(SPECIFIC MATERIALS TO AVOID): Strong acids, oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

5. Environmental and Disposal Information

ACTION TO TAKE FOR SPILLS / LEAKS: Keep spectators away. Floor may be slippery; use care to avoid falling. Contain spills immediately with inert materials (e.g. sand, earth). Transfer liquids and solid diking material to separate suitable containers for recovery or disposal. Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

DISPOSAL METHOD: Dispose off in accordance with Federal, State, County and Local regulations.

6. Health Hazard Data

EYE: Direct contact with the material can cause eye

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-424-9300

Product Code:

Product Name: Edge Kote (various colors)

Effective Date: 03/04/08 Date Printed: 03/04/08 MSDS #:

irritation.

SKIN CONTACT: May cause slight skin irritation on prolonged or repeated skin contact.

INGESTION: May cause gastrointestinal disturbances.

INHALATION: At room temperatures, exposure to vapors or mists are unlikely. Higher temperatures may generate vapors or mists sufficient to cause headache, nausea, irritation of nose, throat and lungs.

SYSTEMIC & OTHER EFFECTS: None known.

7. First Aid

EYES: Flush eyes with a large amount of water for at least 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected skin areas thoroughly with soap and water. Consult a physician if irritation persists.

INGESTION: If swallowed, give two glasses of water to drink. Consult a physician. Never give anything by mouth to an unconscious person.

INHALATION: Move subject to fresh air.

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-424-9300

Product Code:

Product Name: Edge Kote (various colors)

Effective Date: 03/04/08 Date Printed: 03/04/08 MSDS #:

8. Handling Procedures

EXPOSURE GUIDELINE(S): See Section 1 (if any).

VENTILATION: Local exhaust ventilation preferred with a minimum capture velocity of 100 ft/min. at the point of vapor evolution.

RESPIRATORY PROTECTION: None required if airborne concentrations are maintained below the exposure limits listed in Section 1. When the limits are exceeded, wear MSHA/NIOSH approved half-mask, air purifying respirator.

SKIN PROTECTION: Neoprene gloves, aprons.

EYE PROTECTION: Use chemical splash goggles.

9. Additional Information

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep from freezing. The minimum recommended storage temperature for this material is 35 deg.F and the maximum storage temperature is 140 Deg.F.

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-424-9300

Product Code:

Product Name: Edge Kote (various colors)

Effective Date: 03/04/08 Date Printed: 03/04/08 MSDS #:

**REGULATORY INFORMATION: (Not meant to be all-inclusive
- selected regulations represented.)**

NOTICE: The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may n to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations. See MSD Sheet for health and safety information.

U.S. Regulations:

SARA SECTION 313 NOTIFICATION:

This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.