

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204
 Phone #: (414) 271-5011
 Emergency Phone: 1-800-558-1033

Product Code:

Product Name: Fiebing Leather Sheen (aerosol)

Effective Date: 7.29.04 Date Printed: 7.29.04 MSDS #:

1. Ingredients

Name	CAS#	Volatile % by wt	LEL	Vapor Pressure mm Hg. @ 20C	OSHA PEL-PPM	ACGIH TLV-PPM	SARA 313	Carcinogen		
								NTP	IARC	OSHA
*Trichloroethylene	79-01-6	60 – 66	N/A	60.0	50	50	Yes	No	No	No
Xylene	1330-20-7	4 – 6	1.0	5.1	100	100	Yes	No	No	No
Proprietary blend	Mixture	5 – 6	N/A	N/A	-	-	-	-	-	-
Propane	74-98-6	19	2.2	110.0	1000	1000	No	No	No	No
N-butane	106-97-8	6	1.8	17.0	800	800	No	No	No	No

- See Warning in Section 7

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). In addition, other substances not 'Hazardous' per this OSHA Standard may be listed. Where proprietary ingredient shows, the identity may be made available as provided in this standard.

2. Physical Data

% VOLATILE BY VOLUME:	80 - 90
BOILING POINT:	- 43F to 190F
EVAPORATION RATE:	Faster than Ether
VAPOR DENSITY:	Heavier than air
SOLUBILITY IN WATER:	Negligible
SPECIFIC GRAVITY:	1.3746
APPEARANCE:	Clear Spray
ODOR:	Solvent odor

3. Fire And Explosion Hazard Data

DOT PROPER SHIPPING NAME: Consumer commodity ID No. UN1950
 HAZARD CLASS: ORM-D-AIR

FLASH POINT: 12F
 METHOD USED:

FLAMMABLE LIMITS

LEL: See section 1
 UFL:

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-558-1033

Product Code:

Product Name: Fiebing Leather Sheen (aerosol)

Effective Date: 7.29.04 Date Printed: 7.29.04 MSDS #:

EXTINGUISHING MEDIA: Use (NFPA) Class B extinguisher, Carbon dioxide or Foam.

UNUSUAL FIRE & EXPLOSION HAZARDS: Pressure build up due to heat exposure may cause containers to explode. Water may be used to cool ruptured containers.

FIRE-FIGHTING EQUIPMENT/PROCEDURES: Fight fire from safe distance. Wear full protective equipment, including self-contained breathing gear.

LEVEL 3 AEROSOL (NFPA 30 B)

4. Reactivity Data

STABILITY: Stable

CONDITIONS TO AVOID: High temperatures and open flames.

INCOMPATIBILITY(SPECIFIC MATERIALS TO AVOID): Unknown

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, Carbon monoxide

HAZARDOUS POLYMERIZATION: Will not occur

5. Environmental and Disposal Information

ACTION TO TAKE FOR SPILLS / LEAKS: Eliminate all ignition Sources. Provide ventilation. Collect spills with absorbent materials with absorbent materials and non-sparking tools. See Section 8 for protective equipments.

DISPOSAL METHOD: Dispose of in accordance with Federal, State, County and Local regulations. Do not incinerate

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-558-1033

Product Code:

Product Name: Fiebing Leather Sheen (aerosol)

Effective Date: 7.29.04 Date Printed: 7.29.04 MSDS #:

containers.

6. Health Hazard Data (Effects of overexposure)

EYE: Contact may cause redness, irritation, tearing and blurred vision.

SKIN CONTACT: Contact may dry skin causing cracks and irritation.

INGESTION: May be harmful or fatal if swallowed.

INHALATION: (Acute) anaesthetic effect. Irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness or coma.

CHRONIC & OTHER EFFECTS: Reports have associated repeated and prolonged occupational overexposure to solvents with liver, kidney, brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:
Asthma and other respiratory ailments. Chemical sensitization.

7. Emergency and First Aid Procedures

EYES: Immediately flush eyes with water for at least 15 minutes. Get medical attention.

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-558-1033

Product Code:

Product Name: Fiebing Leather Sheen (aerosol)

Effective Date: 7.29.04 Date Printed: 7.29.04 MSDS #:

SKIN: Remove contaminated clothing and shoes. Wash contact area with soap and water. Wash clothing and shoes before reuse.

INGESTION: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a Physician or Poison Control Center immediately.

INHALATION: Remove from exposure of vapors. Administer oxygen if necessary. Call a Physician.

*WARNING: Product contains a chemical(s) known to the State of California to cause cancer, birth defects or other reproductive harm.

8. Handling Procedures

VENTILATION: Supply sufficient ventilation to keep air contaminant concentration below current OSHA(PEL) or ACGIH(TLV).

RESPIRATORY PROTECTION: In open areas with unrestricted ventilation, an OSHA approved respirator to remove solid airborne particles of over spray may be used if prolonged and repeated exposure is likely. In areas with restricted ventilation, the use of OSHA approved chemical/mechanical filter designed to remove both particles and vapors is recommended.

SKIN PROTECTION: Use protective gloves if contact with product is likely.

EYE PROTECTION: Safety glasses

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-558-1033

Product Code:

Product Name: Fiebing Leather Sheen (aerosol)

Effective Date: 7.29.04 Date Printed: 7.29.04 MSDS #:

9. Additional Information

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
Do not store in areas above 100F or near fire or open flames. When storing large quantities, storage conditions should comply with OSHA 1910.106.

OTHER PRECAUTIONS: Prevent prolonged or repeated breathing of vapor or spray mist. Do not take internally. Keep out of reach of children. Use with adequate ventilation.

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204
 Phone #: (414) 271-5011
 Emergency Phone: 1-800-558-1033

Product Code:

Product Name: Fiebing Leather Sheen (aerosol)

Effective Date: 7.29.04 Date Printed: 7.29.04 MSDS #:

REGULATORY INFORMATION: (Not meant to be all-inclusive - selected regulations represented.)

NOTICE: The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations. See MSDS Sheet for health and safety information.

U.S. Regulations:

<u>State</u>	<u>Ingredients</u>	<u>CAS #</u>	<u>% by weight</u>
California	Trichloroethylene	79-01-6	< 66.00000
(Proposition 65)	Residual Butadiene	106-99-0	< 0.00013