

Material Safety Data Sheet

Fiebing Company, Inc., Milwaukee, WI 53204

Phone #: (414) 271-5011

Emergency Phone: 1-800-424-9300

Product Code: SLAC00A013Z

Product Name: Saddle Lac

Effective Date: 03/05/08 Date Printed: 03/05/08 MSDS #:

Please be advised, due to California regulations limiting the VOC content in retail products, this item in your shipment may not be sold to a retail customer. This item, that is bound by these regulations, is intended for commercial use only, and shall not be re-sold nor placed on a retail shelf at any time in the State of California.

1. Ingredients

<u>Name</u>	<u>CAS#</u>	<u>Volatile</u> <u>% by wt</u>	<u>Vapor Pressure</u> <u>LEL</u>	<u>mm Hg. @ 20C</u>	<u>OSHA</u> <u>PEL-PPM</u>	<u>ACGIH</u> <u>TLV-PPM</u>	<u>SARA</u> <u>313</u>	<u>Carcinogen</u> <u>NTP IARC OSHA</u>		
Isopropyl Acetate	108-21-4	20.0	N/A	N/A	250	250	N	N	N	N
Ethyl acetate	141-78-6	17.0	2.2	29.30	400	400	N	N	N	N
Isopropanol	67-63-0	14.0	2.0	33.00	400	400	N	N	N	N
N-butyl acetate	123-86-4	11.0	1.7	8.40	150	150	N	N	N	N
Ethyl alcohol	64-17-5	3.0	2.0	44.00	1000	1000	N	N	N	N
Propane	74-98-6	19	2.2	110.0	1000	1000	N	N	N	N
N-butane	106-97-8	6	1.8	17.0	800	800	N	N	N	N
2-Ethylhexyl Acetate	103-99-3	3.0	N/A	N/A	N/A	N/A	N	N	N	N

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). In addition, other substances not Hazardous per this OSHA Standard may be listed. Where proprietary ingredient shows, the identity may be made available as provided in this standard.

2. Physical Data

% VOLATILE BY VOLUME: 50 - 90
BOILING POINT: - 43F to 340F
EVAPORATION RATE: Faster than Ether
VAPOR DENSITY: Heavier than air
SOLUBILITY IN WATER: Negligible
SPECIFIC GRAVITY: 0.9162
APPEARANCE: Opaque spray
ODOR: Solvent odor

3. Fire And Explosion Hazard Data

DOT PROPER SHIPPING NAME: Consumer commodity ID No. UN1950
HAZARD CLASS: ORM-D-AIR

FLASH POINT: 12F
METHOD USED:

FLAMMABLE LIMITS

LEL: See section 1
UFL:

EXTINGUISHING MEDIA: Use (NFPA) Class B extinguisher, Carbon dioxide or Foam.

UNUSUAL FIRE & EXPLOSION HAZARDS: Pressure build up due to heat exposure may cause containers to explode. Water may be used to cool ruptured containers.

FIRE-FIGHTING EQUIPMENT/PROCEDURES: Fight fire from safe distance. Wear full protective equipment, including self-contained breathing gear.

LEVEL 3 AEROSOL (NFPA 30 B)

4. Reactivity Data

STABILITY: Stable
CONDITIONS TO AVOID: High temperatures and open flames.

INCOMPATIBILITY (SPECIFIC MATERIALS TO AVOID): Unknown

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, Carbon monoxide

HAZARDOUS POLYMERIZATION: Will not occur

5. Environmental and Disposal Information

ACTION TO TAKE FOR SPILLS / LEAKS: Eliminate all ignition Sources. Provide ventilation. Collect spills with absorbent materials with absorbent materials and non-sparking tools. See Section 8 for protective equipments.

DISPOSAL METHOD: Dispose of in accordance with Federal, State, County and Local regulations. Do not incinerate containers.

6. Health Hazard Data (Effects of overexposure)

EYE: Contact may cause redness, irritation, tearing and blurred vision.

SKIN CONTACT: Contact may dry skin causing cracks and irritation.

INGESTION: May be harmful or fatal if swallowed.

INHALATION: (Acute) anaesthetic effect. Irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness or coma.

CHRONIC & OTHER EFFECTS: Reports have associated repeated and prolonged occupational overexposure to solvents with liver, kidney, brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Asthma and other respiratory ailments. Chemical sensitization.

7. Emergency and First Aid Procedures

EYES: Immediately flush eyes with water for at least 15 minutes. Get medical attention.

SKIN: Remove contaminated clothing and shoes. Wash contact area with soap and water. Wash clothing and shoes before reuse.

INGESTION: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a Physician or Poison Control Center immediately.

INHALATION: Remove from exposure of vapors. Administer oxygen if necessary. Call a Physician.

8. Handling Procedures

VENTILATION: Supply sufficient ventilation to keep air contaminant concentration below current OSHA(PEL) or ACGIH(TLV).

RESPIRATORY PROTECTION: In open areas with unrestricted ventilation, an OSHA approved respirator to remove solid airborne particles of over spray may be used if prolonged and repeated exposure is likely. In areas with restricted ventilation, the use of OSHA approved chemical/mechanical filter designed to remove both particles and vapors is recommended.

SKIN PROTECTION: Use protective gloves if contact with product is likely.

EYE PROTECTION: Safety glasses

HYGIENIC PRACTICES: Wash hands before eating or using washroom.

9. Additional Information

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store in areas above 100F or near fire or open flames. When storing large quantities, storage conditions should comply with OSHA 1910.106.

OTHER PRECAUTIONS: Prevent prolonged or repeated breathing of vapor or spray mist. Do not take internally. Keep out of reach of children. Use with adequate ventilation.

10. Transportation Information

DOT PROPER SHIPPING NAME: Consumer Commodity
ID No. : UN 1950
Hazard Class: ORM-D AIR

HMIS INFORMATION

Health - 2
Flammability -4
Reactivity -1